

# Kingtronics®

# BTA16 800B

## FOUR QUADRANT TRIIACS

Blocking Voltage - 800 Volts On-state RMS Current - 16 Ampere

### FEATURES


- ◆ Ultra low gate trigger current.
- ◆ Low cost package.

### APPLICATIONS

Typical applications include motor control, industrial and domestic lighting, heating and static switching.

- ◆ Heating regulation.
- ◆ Motor control.
- ◆ Phase control.

### TO-220




| DIM | Inches |       |       | Millimeters |        |        |
|-----|--------|-------|-------|-------------|--------|--------|
|     | Min    | Type  | Max   | Min         | Type   | Max    |
| A   | 0.591  | -     | 0.646 | 15.000      | -      | 16.400 |
| B   | 0.386  | -     | 0.409 | 9.800       | -      | 10.400 |
| C   | 0.160  | -     | 0.190 | 4.070       | -      | 4.820  |
| D   | 0.500  | -     | 0.562 | 12.700      | -      | 14.270 |
| E   | -      | 0.640 | -     | -           | 16.250 | -      |
| F   | 0.248  | -     | 0.271 | 6.290       | -      | 6.890  |
| R   | 0.140  | -     | 0.156 | 3.560       | -      | 3.960  |
| b1  | 0.030  | -     | 0.037 | 0.750       | -      | 0.950  |
| b2  | 0.095  | -     | 0.105 | 2.420       | -      | 2.660  |
| b3  | 0.046  | -     | 0.054 | 1.170       | -      | 1.370  |
| b4  | 0.046  | -     | 0.054 | 1.170       | -      | 1.370  |
| c1  | 0.017  | -     | 0.023 | 0.420       | -      | 0.580  |
| c2  | 0.091  | -     | 0.115 | 2.320       | -      | 2.920  |
| c3  | 0.045  | -     | 0.055 | 1.150       | -      | 1.390  |
| d1  | 0.100  | -     | 0.120 | 2.540       | -      | 3.040  |
| d2  | 0.125  | -     | 0.155 | 3.180       | -      | 3.930  |

**Kingtronics® International Company**

Website: [www.kingtronics.com](http://www.kingtronics.com) Email: [info@kingtronics.com](mailto:info@kingtronics.com) Tel: (852) 8106 7033 Fax: (852) 8106 7099

**Kingtronics**®**BTA16 800B****FOUR QUADRANT TRIIACS****Blocking Voltage - 800 Volts On-state RMS Current - 16 Ampere****PINNING INFORMATION**

| PIN | Description            | Simplified outline   | Symbol   |
|-----|------------------------|--|--|
| 1   | main terminal 1 ( T1 ) | <br>TO-220 <sup>3</sup> |  |
| 2   | main terminal 2 ( T2 ) |  |  |
| 3   | gate ( G )             |  |  |

**QUICK REFERENCE DATA**

| SYMBOL              | PARAMETER                            | MAX | UNIT |
|---------------------|--------------------------------------|-----|------|
| $V_{DRM}$ $V_{RRM}$ | Repetitive peak off-state voltages   | 800 | V    |
| $I_{T(RMS)}$        | RMS on-state current                 | 16  | A    |
| $I_{TSM}$           | Non-repetitive peak on-state current | 120 | A    |

**THERMAL CHARACTERISTICS**

| SYMBOL       | PARAMETER                                    | CONDITIONS  | MIN | TYP | MAX  | UNIT |
|--------------|--|-------------|-----|-----|------|------|
| $R_{thj-mb}$ | Thermal resistance junction to mounting base | full cycle  | -   | -   | 1.50 | K/W  |
|              |  | half cycle  | -   | -   | 2.00 | K/W  |
| $R_{thj-a}$  | Thermal resistance junction to ambient       | in free air |     | 60  | -    | K/W  |

**LIMITING VALUE**

Limiting values in accordance with the Maximum System(IEC 134).

| SYMBOL       | PARAMETER  | CONDITIONS  | MIN                  | MAX  | UNIT                 |                        |
|--------------|--|---|----------------------|------|----------------------|------------------------|
| $I_{T(RMS)}$ | RMS on-state current   | full sine wave; $T_{mb} \leq 102\text{ }^{\circ}\text{C}$                     | -                    | 16   | A                    |                        |
|              | Non-repetitive peak on-state current                         | full sine wave; $T_j = 25\text{ }^{\circ}\text{C}$ prior to surge             | $t = 20\text{ ms}$   | -    | 120                  | A                      |
|              |  |   | $t = 16.7\text{ ms}$ | -    | 140                  | A                      |
| $I^2t$       | $I^2t$ for fusing  | $t = 10\text{ ms}$  | -                    | 45   | $\text{A}^2\text{s}$ |                        |
| $di_T/dt$    | Repetitive rate of rise of on-state current after triggering | $I_{TM} = 16\text{ A}$ ; $I_G = 0.2\text{ A}$ ;<br>$DI_G/dt = 0.2\text{ A/s}$ | T2+ G+               | -    | 100                  | $\text{A}/\mu\text{s}$ |
|              |  |   | T2- G-               | -    | 100                  | $\text{A}/\mu\text{s}$ |
| $I_{GM}$     | Peak gate current  |   | -                    | 2    | A                    |                        |
| $V_{GM}$     | Peak gate voltage  |   | -                    | 8    | V                    |                        |
| $P_{GM}$     | Peak gate power  |   | -                    | 16   | W                    |                        |
| $P_{G(AV)}$  | Average gate power   | over any 20 ms period   | -                    | 0.35 | W                    |                        |
| $T_{stg}$    | Storage temperature  |   | -40                  | 150  | $^{\circ}\text{C}$   |                        |
| $T_j$        | Junction temperature   |   | -40                  | 125  | $^{\circ}\text{C}$   |                        |

**Kingtronics**® International Company

**Kingtronics**®**BTA16 800B****FOUR QUADRANT TRIIACS****Blocking Voltage - 800 Volts On-state RMS Current - 16 Ampere****CHARACTERISTICS**T<sub>J</sub> = 25°C unless otherwise stated

| SYMBOL                         | PARAMETER  | CONDITIONS   | MIN    | TYP  | MAX  | UNIT |    |
|--------------------------------|--|--|--------|------|------|------|----|
| <b>Static characteristics</b>  |  |  |        |      |      |      |    |
| I <sub>GT</sub>                | Gate trigger current                                 | V <sub>D</sub> = 12 V; I <sub>T</sub> = 0.1A   | T2+ G+ |      | 10   | 25   | mA |
|                                |  |  | T2+ G- |      | 15   | 25   | mA |
|                                |  |  | T2- G- |      | 15   | 25   | mA |
|                                |  |  | T2- G+ |      | 30   | 50   | mA |
| I <sub>L</sub>                 | Latching current                                     | V <sub>D</sub> = 12 V; I <sub>GT</sub> = 0.1A  | T2+ G+ | -    | 20   | 50   | mA |
|                                |  |  | T2+ G- | -    | 30   | 80   | mA |
|                                |  |  | T2- G- | -    | 20   | 50   | mA |
|                                |  |  | T2- G+ |      | 20   | 50   | mA |
| I <sub>H</sub>                 | Holding current                                      | V <sub>D</sub> = 12 V; I <sub>GT</sub> = 0.15A   | -      | 20   | 40   | mA   |    |
| V <sub>T</sub>                 | On-state voltage                                     | I <sub>T</sub> = 20A   | -      | -    | 1.85 | V    |    |
| V <sub>GT</sub>                | Gate trigger voltage                                 | V <sub>D</sub> = 12 V; I <sub>T</sub> = 0.1A   | T2+ G+ | 0.50 | 0.78 | 1.50 | V  |
|                                |  |  | T2+ G- | 0.50 | 0.70 | 1.50 | VV |
|                                |  |  | T2- G- | 0.50 | 0.71 | 1.50 | VV |
|                                |  |  | T2- G+ | 0.50 | 0.81 | 2.00 | V  |
| <b>Dynamic Characteristics</b> |  |  |        |      |      |      |    |
| dVD/dt                         | Critical rate of rise of off-state voltage           | V <sub>DM</sub> = 67% V <sub>DRM(max)</sub> ; T <sub>j</sub> = 125 °C; Exponential wave form; gate open circuit                                    | 250    | 500  | -    | V/μs |    |
| dIcom/dt                       | Critical rate of change of commutating current       | V <sub>D</sub> = 400 V; T <sub>j</sub> = 125 °C<br>I <sub>T(RMS)</sub> =4.4A;<br>Commutatingdv/dt = 18 V/ s,<br>Without snubber; gate open circuit | 6.50   | -    | -    | A/ms |    |
| dI/dt                          | Repetitive Critical Rate of Rise of On-State Current | I <sub>PK</sub> = 50 A; PW = 40 sec; di <sub>G</sub> /dt =200 mA/ sec; f = 60 Hz   | -      | -    | 10   | A/μs |    |

**Kingtronics**® International CompanyWebsite: [www.kingtronics.com](http://www.kingtronics.com) Email: [info@kingtronics.com](mailto:info@kingtronics.com) Tel: (852) 8106 7033 Fax: (852) 8106 7099

# Kingtronics®

# BTA16 800B

## RATINGS AND CHARACTERISTIC CURVES BTA16 800B




Fig. 1. Maximum on-state dissipation,  $P_{tot}$ , versus rms on-state current,  $I_{T(RMS)}$ , where  $\alpha$  = conduction angle.




Fig. 4. Maximum permissible rms current  $I_{T(RMS)}$ , versus mounting base temperature  $T_{mb}$ .




Fig. 2. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$  versus pulse width  $t_p$  for sinusoidal currents,  $t_p \leq 20\text{ms}$ .




Fig. 5. Maximum permissible repetitive rms on-state current  $I_{T(RMS)}$ , versus surge duration, for sinusoidal currents,  $f = 50\text{ Hz}$ ;  $T_{mb} \leq 99^\circ\text{C}$ .




Fig. 3. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$ , versus number of cycles, for sinusoidal currents,  $f = 50\text{ Hz}$ .










Fig. 6. Normalised gate trigger voltage  $V_{GT}(T_j)/V_{GT}(25^\circ\text{C})$ , versus junction temperature  $T_j$ .

**Kingtronics® International Company**

# Kingtronics®

# BTA16 800B

## RATINGS AND CHARACTERISTIC CURVES BTA16 800B



Note: Specifications are subject to change without notice.

**Kingtronics® International Company**

Website: [www.kingtronics.com](http://www.kingtronics.com) Email: [info@kingtronics.com](mailto:info@kingtronics.com) Tel: (852) 8106 7033 Fax: (852) 8106 7099