


Kingtronics®**D3UB05 THRU
D3UB100****Single Phase 3.0 AMPS. Glass Passivated Bridge Rectifiers****Voltage Range 50 to 1000 Volts Current 3.0 Amperes****FEATURES**

- ◆ Ideal for printed circuit boards
- ◆ Reliable low cost construction technique results in inexpensive product
- ◆ High temperature soldering guaranteed:
260°C / 10 seconds

MECHANICAL DATA

- ◆ Case: Molded plastic
- ◆ Lead: solder plated
- ◆ Polarity: As marked on body
- ◆ Mounting Torque: 0.8N·m
- ◆ Recommended Torque: 0.5N·m

Package: D3K

Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%

Type Number		D3UB 05	D3UB 10	D3UB 20	D3UB 40	D3UB 60	D3UB 80	D3UB 100	UNITS
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at T _C = 100°C T _A = 40°C	I _{F(AV)}				3.0 ⁽¹⁾				A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}				60				A
Maximum Instantaneous Forward Voltage @ 3A	V _F				1.1				V
Rating for fusing (3ms≤t<8.3ms) T _J =25°C	I ² t				15				A ² sec
Maximum DC Reverse Current @ T _A =25°C rated DC blocking voltage per leg T _A = 125°C	I _R				5.0				μA
Typical Thermal Resistance (Note)	R _{θJA} R _{θJL}				40 15				°C/W
Operating Temperature Range	T _J				-55 to +150				°C
Storage Temperature Range	T _{STG}				-55 to +150				°C

NOTE: 1. Unit case mounted on 1.6*1.6*0.06" thick (5.1*5.1*0.15cm) Al.Plate

2. Unit mounted on P.C.B. with 0.5*0.5" (12.7*1.27mm) copper pads and 0.375" (9.5mm) lead length

Kingtronics® International Company

Kingtronics®

D3UB05 THRU D3UB100

RATING AND CHARACTERISTIC CURVES D3UB05 THRU D3UB100

FIG. 1-MAXIMUM NONO-REPETITIVE FORWARD SURGE




FIG. 2-MAXIMUM FORWARD CURRENT DERATING CURVE





FIG. 3-TYPICAL INSTANTANEOUS FORWARD


CHARACTERISTICS PER BRIDGE ELEMENT



INSTANTANEOUS FORWARD VOLTAGE.(V)

FIG. 4-TYPICAL REVERSE CHARACTERISTICS PER

BRIDGE ELEMENT



PERCENT OF RATED PEAK REVERSE VOLTAGE.(%)

Note: Specifications are subject to change without notice.

Kingtronics® International Company

Website: www.kingtronics.com Email: info@kingtronics.com Tel: (852) 8106 7033 Fax: (852) 8106 7099