



# Kingtronics®

## FKT-AA

### METALLIZED POLYESTER FILM CAPACITOR - AXIAL

#### HOW TO ORDER

<u>FKT</u>	<u>AA</u>	<u>2A</u>	<u>103</u>	<u>K</u>	<u>000</u>	<u>000</u>	<u>B</u>	<u>R</u>
Series	Sub Series	Voltage	Capacitance	Capacitance Tolerance	Axial	Lead Length	Packing	Pb
		1.	2.	3.	4.	5.	6.	7.

#### NOTE:

##### 1. Voltage

Code	1H	1J	2A	2C	2D	2E	2G	2J	3A	3C	3D	3F
Voltage	50V	63V	100V	160V	200V	250V	400V	630V	1000V	1600V	2000V	3000V
Code	E2	P2	Q1	Q2	Q3	G2						
Voltage	250 VAC	275 VAC	300 VAC	305 VAC	310 VAC	400 VAC						

##### 2. Capacitance

Code	102	103	104	105	106	222	223	224	225
Capacitance	1000pF	0.01 $\mu$ F	0.1 $\mu$ F	1 $\mu$ F	10 $\mu$ F	2200pF	0.022 $\mu$ F	0.22 $\mu$ F	2.2 $\mu$ F
Code	332	333	334	472	473	474	682	683	684
Capacitance	3300pF	0.033 $\mu$ F	0.33 $\mu$ F	4700pF	0.047 $\mu$ F	0.47 $\mu$ F	6800pF	0.068 $\mu$ F	0.68 $\mu$ F

##### 3. Capacitance Tolerance

Code	J	K	M
Tolerance	$\pm$ 5%	$\pm$ 10%	$\pm$ 20%

##### 4. Axial

Code	000
Axial	Standard

##### 5. Lead Length

Code	000
Lead Length	Standard

##### 6. Packing

Code	B
Packing	Bulk

##### 7. Pb

Code	R
Pb	RoHS

Note: Specifications are subject to change without notice.

**Kingtronics® International Company**

Website: [www.kingtronics.com](http://www.kingtronics.com)

Email: [info@kingtronics.com](mailto:info@kingtronics.com)

Tel: (852) 8106 7033

Fax: (852) 8106 7099