


SWITCHING TRANSISTOR



Marking: 2A

Suggested Layout


SOT-23



Top view



Dimension



DIM	Millimeters
A	2.85~3.04
B	1.30±0.10
C	1.00±0.10
D	0.45±0.05
E	2.25~2.55
G	1.90±0.1
K	0.00-0.10
M	0.20 min
N	0.60±0.10
P	7±2°

MAXIMUM RATINGS (Ta=25°C)

Characteristic	Symbol	Rating	Unit
Collector-Emitter Voltage	V_{CEO}	-40	Vdc
Collector-Base Voltage	V_{CBO}	-40	Vdc
Emitter-Base Voltage	V_{EBO}	-5	Vdc
Collector Current - Continuous	I_C	-200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board (1) (Ta=25°C)	P_D	225	mW
Derate above 25°C		1.8	mW/°C
Thermal Resistance Junction to Ambient	R_{JA}	556	°C/W
Total Device Dissipation Alumina Substrate, (2) Ta=25°C	P_D	300	mW
Derate above 25°C		2.4	mW/°C
Thermal Resistance Junction to Ambient	R_{JA}	417	°C/W
Junction and Storage Temperature	T_J , T_{stg}	150, -55~150	°C

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Characteristic	Symbol	Test Condition	Min	Type	Max	Unit
Collector Cutoff Current	I_{CEX}	$V_{CE}=-30V_{dc}$, $V_{EB}=-3.0 V_{dc}$	--	--	-50	nAdc
Base Cutoff Current	I_{BEX}	$V_{CE}=-30V_{dc}$, $V_{EB}=-3.0V_{dc}$	--	--	-50	nAdc


Kingtronics®**CDS3906-ME**

Collector-Emitter Breakdown Voltage (3)	$V_{(BR)CEO}$	$I_C=-1.0mA_{dc}, I_B=0$	-40	--	--	Vdc
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=-10\mu A_{dc}, I_E=0$	-40	--	--	Vdc
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=-10\mu A_{dc}, I_C=0$	-5	--	--	Vdc
DC Current Gain	h_{FE}	$I_C=-0.1mA_{dc}, V_{CE}=-1.0V_{dc}$	60	--	--	--
		$I_C=-1.0mA_{dc}, V_{CE}=-1.0V_{dc}$	80	--	--	
		$I_C=-10mA_{dc}, V_{CE}=-1.0V_{dc}$	100	--	300	
		$I_C=-50mA_{dc}, V_{CE}=-1.0V_{dc}$	60	--	--	
		$I_C=-100mA_{dc}, V_{CE}=-1.0V_{dc}$	30	--	--	
Collector-Emitter Saturation Voltage (3)	$V_{CE(sat)}$	$I_C=-10mA_{dc}, I_B=-1.0mA_{dc}$	--	--	-0.25	Vdc
		$I_C=-50mA_{dc}, I_B=-5.0mA_{dc}$	--	--	-0.4	
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=-10mA_{dc}, I_B=-1.0mA_{dc}$	-0.65	--	-0.85	Vdc
		$I_C=-50mA_{dc}, I_B=-5.0mA_{dc}$	--	--	-0.95	
Current-Gain-Bandwidth Product	f_T	$I_C=-10mA_{dc}, V_{CE}=-20V_{dc}, f=100MHz$	250	--	--	MHz
Output Capacitance	C_{obo}	$V_{CB}=-5.0V_{dc}, I_E=0, f=1.0MHz$	--	--	4.5	pF
Input Capacitance	C_{ibo}	$V_{EB}=-0.5V_{dc}, I_C=0, f=1.0MHz$	--	--	10	pF
Input Impedance	h_{ie}	$V_{CE}=-10V_{dc}, I_C=-1.0mA_{dc}, f=1.0KHz$	1.0	--	10	k Ω
Voltage Feedback Ratio	h_{re}	$V_{CE}=-10V_{dc}, I_C=-1.0mA_{dc}, f=1.0KHz$	0.5	--	8.0	$\times 10^{-4}$
Small-Signal Current Gain	h_{fe}	$V_{CE}=-10V_{dc}, I_C=-1.0mA_{dc}, f=1.0KHz$	100	--	400	
Output Admittance	$*h_{oe}$	$V_{CE}=-10V_{dc}, I_C=-1.0mA_{dc}, f=1.0KHz$	1.0	--	60	$\mu mhos$
Noise Figure	NF	$V_{CE}=-5.0V_{dc}, I_C=-100\mu A, R_S=1.0K\Omega, f=1.0KHz$	--	--	4.0	dB
Delay Time	t_d	$V_{CC}=-3.0V_{dc}, V_{BE}=0.5V_{dc}$	--	--	35	nS
Rise Time	t_r	$I_C=-10mA_{dc}, I_{B1}=-1.0mA_{dc}$	--	--	35	
Storage Time	t_s	$V_{CC}=-3.0V_{dc}, I_C=-10mA_{dc}$	--	--	225	nS
Fall Time	t_f	$I_{B1}=I_{B2}=-1.0mA_{dc}$	--	--	75	

- FR-5=1.0x0.75x0.062in.
- Alumina=0.4x0.3x0.024in, 99.5% alumina.
- Pulse Width $\leq 300\mu S$; Duty Cycle $\leq 2.0\%$.
-



Kingtronics® International Company

Typical Performance Characteristics










TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

($V_{CE} = -5.0\text{ Vdc}$, $T_A = 25^\circ\text{C}$, Bandwidth = 1.0 Hz)



Kingtronics®

CDS3906-ME



Note: Specifications are subject to change without notice.

Kingtronics® International Company